

# IEC LOCK

## NEW C14 IEC LOCK+ DUAL LOCKING CONNECTOR



### Technical Information

#### General Information

- Secure Locking Side and Bottom Tabs
- C14 Connector cannot be accidentally pulled or vibrated out of the outlet
- A European, USA, Canada, Australian, and Japanese approved Dual Locking C14 IEC LOCK
- Connector to ensure compatibility with a wide range of standard non locking C13 outlets.

#### Cable Size

- 3 Core 0.75mm<sup>2</sup>, 1.00mm<sup>2</sup>, 1.5mm<sup>2</sup> H05VV-F, H05RN-F, H05BB-F, H05Z1Z1-F (Europe)
- 3 x 18AWG, 16AWG, 14AWG SVT, SVTO, SVTOO, SJT, SJTW, SJTO, SJTOW, SJTOO, SJTOOW, SJ, SJO, SJOO, SJOW, SJOOW, SJE, SJEO, SJEOO, SJEW, SJEOW, SJEOWW (America & Canada)
- 3 x 0.75mm<sup>2</sup>, 1.00mm<sup>2</sup>, 1.5mm<sup>2</sup> H05VV-F, H05RN-F, H05Z1Z1-F (Australia)
- 3 x 1.25mm<sup>2</sup>, 2.00mm HVCTF (Japan)

#### Rating

- 10A / 250V~ (Europe & Australia)
- 15A / 250V~ (America, Canada & Japan)

#### Test Information

**Test Body:** DEKRA (KEMA), UL, SAA, PSE

**Test Standard:** EC/EN 60320-1: 2015 (Europe)

UL 60320-1 & C22.2 No. 21-18 (America & Canada)

AS/NZS 60320.1:2012 (Australia)

Technical Requirements by the METI Ordinance, Appendix 4 Section 1, 6 + Appendix 10 Chapter 5 (Japan)

#### Patent Information

Patent Pending