

# PS/2-USB Virtual Media Console Module

## KA7240S

- The KA7240S Console Module offers secure access to the servers in a Matrix KVM Switch (KM0932/KM0532) from a PS/2 or USB console (monitor, keyboard, and mouse) up to 200 meters away. It provides an extra computer port for integration with a computer workstation, enabling users to seamlessly switch between the local computer and the servers in the Matrix KVM Switch. The KA7240S also features an intuitive graphical user interface, the Graphical OSD, with easy-to-use menus and icons that enable easy access and efficient management.


KA7240S has a built-in RS-232 port. Administrators can establish a serial terminal login to the Console Module in order to control the KVM port access for all consoles connected to switch – any console can be assigned to access any KVM port from a single interface point. This function is extremely useful in large data centers where the display of all the consoles can be projected onto a wall for easy viewing of all operations, and the entire installation can be monitored on a port-by-port basis.

In addition, the KA7240S features an automatic skew compensation function, which corrects color phase and timing errors that occur over long distance transmissions.



### Features

- One Combo Graphic Console Module can control a local computer and a matrix KVM switch (KM0932/KM0532)
- USB Virtual Media Support
- Audio enabled
- Enhanced video quality via automatic skew compensation support
- Supports PS/2 and USB keyboards and mice (Console)
- Switch between your workstation computer and the matrix KVM switch
- Graphical OSD-intuitive, easy-to-use graphical On Screen Display to manage servers
- RS-232 port login support permits an administrator to control the KVM port access for all consoles connected to switch – any console can be assigned to access any KVM port from a single interface point
- Connects to matrix KVM switch via Cat 5e/6 cable
- Superior video quality – 1280 x 1024 @ 60Hz for up to 200 m
- Manual video gain control for fine tuning
- Convenient computer selection via intuitive hotkey combinations or graphical OSD menus
- Firmware upgradeable



### Specifications

Function		KA7240S	
Computer Connections		1	
Console Connections		1	
Port Selection		GUI, Hotkey	
Connectors	Console Ports	Keyboard	1 x USB Type A Female (White) 1 x 6-pin Mini-DIN Female (Purple)
		Video	1 x HDB-15 Female (Blue)
		Mouse	1 x USB Type A Female (White) 1 x 6-pin Mini-DIN Female (Green)
		Local Computer KVM Port	1 x SPHD-17 Female (Yellow)
	USB Virtual Media 2.0 Port	1 x USB Type A Female (White)	
	KVM Switch Ports	2 x RJ-45 Female	
	RS-232	1 x DB-9 Male (Black)	
Audio	2 x Mini Stereo Jack Female (Green) 2 x Mini Stereo Jack Female (Pink)		
	Power	1 x DC Jack	
	Switches	Local/Remote Selection	1 x Pushbutton
Firmware Upgrade		1 x Slide	
Video Gain Adjustment		2 x Pushbutton	
LEDs	Power	1 (Blue)	
	Online	1 (Green)	
	Local	1 (Orange)	
	Remote	1 (Orange)	
Emulation	Keyboard / Mouse	PS/2; USB (PC, Sun, Mac)	
Video	1280 x 1024 @ 60Hz (200m max.)		
Scan Interval	1 - 240 Seconds		
Power Consumption	DC 5.3V, 10.12W		
Environment	Operating Temperature	0° to 50° C	
	Storage Temperature	-20° to 60° C	
	Humidity	0 - 80% RH, Non-condensing	
Physical Properties	Housing	Metal	
	Weight	1.26 kg	
	Dimensions (L x W x H)	22.71 x 17.15 x 5.48 cm	

### ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijih District., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
 www.aten.com E-mail: marketing@aten.com

Publish Date: 06/2017 V1.0



© Copyright 2017 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their respective owners.